



This Instruction Manual is provided as a guide for the Sentry Guarding System Accessories. All accessories are designed to provide safe, fast and cost effective solutions to your guarding projects. All accessories are compliant to Australian Standards. Accessory applications are not limited to examples shown in this Instruction Manual, however weight and force limits should be considered. **Product may fail and void warranty if guarding is not correctly assembled and installation does not comply with standards, design guide and drawings.**

Safety & General Information




OPENING GUIDE

As per AS/NZ 4024.3610/3611



| Opening (A) mm | Distance (B) mm | | |
|----------------|-----------------|--------|-------|
| | Slot | Square | Round |
| 6 < A ≤ 8 | ≥ 20 | ≥ 15 | ≥ 5 |
| 8 < A ≤ 10 | ≥ 80 | ≥ 25 | ≥ 20 |
| 10 < A ≤ 12 | ≥ 100 | ≥ 80 | ≥ 80 |
| 12 < A ≤ 20 | ≥ 120 | ≥ 120 | ≥ 120 |




| Opening (A) mm | Distance (B) mm | | |
|----------------|-----------------|--------|-------|
| | Slot | Square | Round |
| 20 < A ≤ 30 | ≥ 850* | ≥ 120 | ≥ 120 |

* If the length of the slot opening is less than or equal to 65mm, the thumb will act as a stop and safety distance can be reduced to 200mm.

MESH CLAMP BRACKET

Part Number: **SGS_MCB_001**


The Mesh Clamp Brackets clamp infill sections or extensions to the Guarding panel, allowing openings in the mesh to be closed on site, or extensions to be added. This eliminates hot works and reduces fabrication and installation time.




Application Example



Mesh extension fast fix




Sheet metal extension design fix



Arrangement to fix non-compliant 50mm gap

MESH CLAMP BRACKET INSTALLATION



Step 1


Measure and cut mesh to enclose opening with enough green to overlap on existing mesh.

For optimum strength, keep Mesh Clamp Brackets at a maximum of 500mm apart.




Step 2

Hook the top of the Mesh Clamp Bracket onto the back wire and swing the bottom into position.



Step 3

Lightly tighten the M6 cap screw to keep the Mesh Clamp Bracket in place allowing the mesh to be adjusted. Secure the mesh with adequate quantity of Mesh Clamp Bracket.



Step 4

Mesh infill panel can be adjusted in the horizontal or vertical direction to comply with the minimum gap. Depending on panel adjustment direction, the Mesh Clamp Bracket can be installed in a vertical or horizontal direction to allow desired adjustment. Once in place, all cap screws can be tightened to 9.5Nm.



AS/NZS
4024.3610/3611



STRENGTH
TESTED



EASY
INSTALLATION



MODULAR
SYSTEM



COST SAVING
UP TO 30%



Certified System
Quality
ISO 9001

Certified System
Environment
ISO 14001




Certified System
OHS
ISO 45001

CONDITION MONITORING GUARD INSERT

Part Number: **SGS_CMG_001** - Square option - Shown below

Part Number: **SGS_CMG_002** - Round option - Available

The Condition Monitoring Guard Insert provides a safer way for workers to do their periodic inspection by providing a physical barrier between the human hand and machinery. A Guard End Cover is also provided for side access monitoring points.



Step 1

Mark and cut a 150x150mm area for the square option or 250x250mm for the round option on grid mesh at location directly inline with monitoring point. Touch up exposed wire with yellow paint.

Step 2

Measure distance from guarding to monitoring point. Cut Condition Monitoring Guard inline to nearest vertical wire if required. Refer to opening guide and AS/NZ 4024.3610/3611 to comply.

Step 3


Secure Condition Monitoring Guard with the four Mesh Clamp Brackets provided. This is also applicable for the round Condition Monitoring Guard option.

Securing Guard End Cover

Place Guard End Cover at the end of Condition Monitoring Guard Insert and align centrally. Bend opposite tabs simultaneously over mesh wire and repeat to all to secure onto Condition Monitoring Guard. Guard End Cover can be cut to suit specific scenario.

BOLT SIGN BRACKET

Part Number: **SGS_BSB_001**



The Bolt Sign Bracket is suitable for removable guarding and high vibration areas. The Bolt Sign Bracket can be orientated both vertically and horizontally.

Step 1

Place the sign in the centre of the guard panel and mark locations for the Bolt Sign Brackets.

Step 2

Slide the bottom end of the Bolt Sign Bracket over the wire and hinge inwards to clip top section onto top wire.

Step 3

Place sign over M4 stud and secure with Nyloc nut.

Note: Due to the mesh grid tolerance, both the Bolt Sign Bracket and Rivet Sign Bracket may need to be orientated either vertically or horizontally.

RIVET SIGN BRACKET

Part Number: **SGS_RSB_001**

The Rivet Sign Bracket offers a fast and permanent fixture suitable for fixed guarding and areas with minimal or no vibration.



Step 1

Attach the Rivet Sign Bracket to the guard panel as per bolt option (Steps 1 & 2 above).

Step 2

Place sign on top of Rivet Sign Bracket and secure with 5.4 Stainless Steel rivet (Ø4.0mm, 6.4mm grip).



CONTACT US:

43A Sparks Road, Henderson, WA 6166
P (08) 9418 7725 E productdesign@cadds.com.au
ABN 79 060 988 767

sentryguardingsystem.com.au



AS/NZS
4024.3610/3611



STRENGTH
TESTED



EASY
INSTALLATION



MODULAR
SYSTEM



COST SAVING
UP TO 30%



Certified System
Quality
ISO 9001

Certified System
Environment
ISO 14001

Certified System
OHS
ISO 45001

